

# Del-Ron<sup>®</sup>



## Synthetic Heavy Duty Diesel Engine oil 5w40

The oil: **real synthetic** formulation; **PolyAlphaOlefin (PAO)**.

Manufactured using a high stability viscosity improver. This way the oil has achieved **superior qualities; high stability and stability under stress, good endurance against high temperatures and good properties of diminishing the wearing of engine parts and "Low-Friction" ability to lower fuel consumption.**

For long oil change intervals. **Very good soot dissolving property, your engine will stay clean longer and reduces cylinder polish.**

Suitable for exhaust after treatment devices, **SAPS 1%, Phosphorous 0,08%**  
**Suitable for Older Diesels (E4) and Newest High Power clean tech. engines (E9) !**  
**Do not mix with other oils or additives !**

**Technical data:**

<b>SAE:</b>	<b>5w40</b>
<b>Visc. +40C, cSt</b>	<b>84</b>
<b>Visc. +100C, cSt</b>	<b>13,2</b>
<b>Visc.index:</b>	<b>157</b>
<b>Visc.CCS(-30C 5w)</b>	<b>6.500 mPas</b>
<b>Pour point:</b>	<b>-45 C</b>
<b>HTHS (+150C)</b>	<b>3,65 mPas</b>
<b>Sulphate ash(SAPS):</b>	<b>1,0 %</b>
<b>Phosphorous:</b>	<b>0,08 %</b>
<b>TBN</b>	<b>12,0</b>
<b>Colour:</b>	<b>Red</b>

<b>ACEA: E4, E6, E7, E9</b>
<b>API: CI-4, CJ-4</b>
<b>CAT: ECF-3</b>
<b>DAF: Extended Drain</b>
<b>Deutz: DQC-IV-10 LA</b>
<b>Detroit Diesel: 93K218</b>
<b>JASO: DH-2</b>
<b>Mack: EO-O Premium Plus</b>
<b>MB: p228.51, 235.31</b>
<b>MAN: M3477, M3575, M3271-1</b>
<b>MTU: Category 3.1</b>
<b>Renault: RLD-3</b>
<b>Scania: Low Ash, LA-2, LDF-3</b>
<b>Volvo: VDS-4</b>

Values may vary/change, Please note that the properties do not constitute a specification and are not an warranty or guarantee of any properties.

