



A Full synthetic 2-Stroke motor oil, based on synthetic esters.

Manufactured for demanding 2-T lubrication; high power, high temperatures and high rpm's.

Very good properties for minimizing engine wear, cylinder&piston and bearings.

Low ash content (low ash deposit, SAPS 0,08%) with low smoke formation helps to keep your engine clean and efficient.

Suitable for both 2-T motorcycles and snowmobiles. Excellent for race use and normal everyday use too.

Helps to increase performance and reduce engine's internal friction.

May be used as premixed at fuel or injection/autolube systems.

Remember to check the engine manufacturers recommendation of correct fuel and 2-T oil ratio. Remember, in Finland, mixing with fuel causes excise duty, fuel tax, Law 767/2020 for fuel tax, Finland.



## JASO-FD, ISO-L-EGD, API-TC

## Technical:

Visc. +40c, cSt	50
Visc. +100c, cSt	8
Pour point, C°	- 42
Flash point, C°	+70 min.
Density +15 C°	0,9
Sulphate ash -	
content (SAPS) %	0,08
Colour:	Violetti

Values may vary/change, Please note that these properties do not constitute a specification and are not an warranty or gurantee of any properties.





Fettekno Oy, Tuulissuontie 35, 21420 Lieto, Finland, www.fettekno.fi, fettekno@kolumbus.fi, tel.02-4877953